Automated Attendance System through Eigen Faces Using Image Processing

M. Sree Vidya*, K. Arul

Department of Computer Science and Engineering, Saveetha School of Engineering, Saveetha University, India

Article Info	ABSTRACT
Article history:	Eigen faces (PCA) approach for face recognition. The face is an important
Received August 2, 2016 Revised October 7, 2016 Accepted November 1, 2016	part of which you are how people identify you. In face recognition there are two types of comparisons verification and identification. There are about 80 nodal points on a human face here are few nodal points that are measured by software that are distance between eyes, width of the nose, Depth of the eye socket, Check bones, Jaw line and Chin By this method we can take
Keyword:	automatic attendance .face recognition is done by projecting new image onto a low dimensional linear "face space" defined by the Eigen faces. This method is reliable, low cost, faster access and reduces man power.
Eigen Faces	
Nodal Points	
Recognition	Copyright $@$ 2016 Institute of Advanced Engineering and Science. All rights reserved.
Corresponding Author:	

Meduri Sree Vidya, Department of Computer Science and Engineering Saveetha School of Engineering, Saveetha University, India Email: munnisrividya123@gmail.com

1. INTRODUCTION

Eigen faces refer to an appearance-based approach to face recognition that seeks to capture the variation in a collection of face images and utilize this data to encode and analyze images of individual faces in a holistic manner. Eigen faces is probably one of the simplest face recognition methods and also rather old, then why worry about it at all? Because it is simple it works quite well. And its simplicity also makes it a good way to understand how face recognition/dimensionality reduction extra works.

Facial acknowledgment technologies can recognize identity of an individual even without any direct communication between the system and the user. This is conventionally done by taking or capturing a sample of image of the individual using cameras.

Biometrics supports in authenticating the character of an individual through physiological or behavior distinctiveness further precisely, conventional authentication methods such as magnetic cards, passwords, keys and personal identification cards are pathetic towards any threat and can be stolen without much effort. Biometrics technology acknowledges an extends a simple and secure authentication.

2. LITERATURE SURVEY

a. Comparison of the two approaches:

In Nearest neighbor training time is much faster, storage is same, classification time is slightly slower. Accuracy: neutral network is able to achieve the same accuracy using 5 Eigen faces with nearest neighbor using 15, and a higher accuracy when using 15.

b. PCA

Main statement of PCA approach:

1. Face space forms a group in image space.

2. PCA gives appropriate representation.

- Eigen Face approach:
- c. Eigen Space and Eigen Faces

Face images are projected into a feature space ("Face Space") that best encodes the difference among known face pictures.

The face space is defined by the "Eigen faces", where Eigen faces are the set of faces in Eigenvectors

- d. Steps for Face Recognition
 - 1. Initialization
 - 2. Acquire the training set and calculate Eigen faces (using PCA projections) which define Eigen space.
 - 3. When a new face is encountered, calculate its weight.
 - 4. Determine if the image is face.
 - 5. If yes, categorize the weight pattern as known or unknown.
 - 6. (Learning) if the same unknown face is seen many times integrate it into known faces.
- e. Statement
 - 1. Given an image, to identify it as a face and/or extract face image from it.
 - 2. To retrieve the similar pictures from the given database of face images.
- f. Face recognition has different potential applications, such as
 - 1. Person identification
 - 2. Human-computer interaction
 - 3. Security system
- g. Stages of face recognition:
 - 1. Face location detection
 - 2. Feature extraction
 - 3. Facial image classification
- h. Aroaches of feature extraction:
 - 1. Local: Distance between eyes, width of the nose, mouth information easily affected by irrelevant information.
 - 2. Global: Extract feature from whole image
- i. Eigen Face Space:

Face recognition is done by projecting new image onto a low dimentional linear "face space" defined by the Eigen faces.

3. IMPLIMENTATION

3.1. Eigen face Method with PCA:

- a. Main assumption of PCA approach:
 - 1. Face space forms a group in image space.
 - 2. PCA gives appropriate representation
- b. Principal Component Analysis (PCA):
 - 1. A N x N pixel picture of a face, represented as a vector occupies a single point in N2dimensional picture space.
 - 2. Images of faces being alike in overall configuration will not be randomly distributed in this enormous picture space.
 - 3. Therefore, they can be defined by a low dimensional subspace.
 - 4. Foremost hint of PCA for faces:
 - 5. To find vectors that best account for variation of face picture in entire picture space these vectors are known as Eigenvectors.
 - 6. Construct a face space and project the picture into this face space (Eigen faces), as shown in Figure 1.



Figure 1. Face Space (Eigen faces).

Picture Representation:

Training set of m images of size N^*N are represented by vectors of size $N^2 x_1, x_2, x_3, ..., x_M$ as shown Figure 2.



Figure 2. Picture Representation



Average picture and difference picture:

The average training set of average picture as shown in Figure 3 is defined by

m= (1/m) $\sum_{i=1}^{m} x_i$



Figure 3. Average Picture

Each face differs from the average by vector

 $r_i = x_i - m$

1) Eigenvalues and Eigenvectors If v is a nonzero vector and λ is a number such that $Av = \lambda v$, then v is said to be an eigenvector of A with eigenvalue λ . Example:



- c. Limitations of Eigen faces Approach
 - Variations in Lighting Conditions (Figure 4) Different lighting conditions for enrolment and query. Bright light causing image saturation.



Figure 4. Variations in Lighting Conditions

- 2. Differences in pose-Head orientation 2D feature distances appear to distort.
- 3. Expression Change in feature location and shape.

3.2. Calculation of Eigenfaces

- 1) Compute average face: v.
- 2) Gather **difference between training images** and average face in the matrix A (M by N), where M is the number of pixels and N is the number of pictures.

$$A = [u_1^1 - v, \dots, u_n^1 - v, \dots, u_1^p - v, \dots, u_n^p - v]$$

3) Eigenvectors of covariance matrix C (M by M) produce the eigenfaces.

 $C = A^T A$

M is generally big, so this procedure would be time consuming.

3.3. Calculation of the Eigenvectors of C

If number of data points is smaller than the dimension (N<M), then there will be N-1 meaningful Eigenvectors. Instead of directly calculating the Eigenvectors of C, we shall calculate the Eigenvalues and the corresponding Eigenvectors of a smaller matrix L (N by N)

if λi are Eigenvectors of L then A λi are Eigenvectors for C.

The Eigenvectors are in the descent order of corresponding eigenvalues.

$$L = {}^{T}AA \qquad \qquad L = {}^{Y}AA$$

3.4. Representation of Face Pictures using Eigen Faces:

The training face pictures and new face pictures can be represented as linear combination of the Eigen faces.

$$\iota = \sum_{i} \mathcal{A}_{i}$$

when we have a face image of *u*: Since the Eigenvectors are orthogonal :

$$q = \mathcal{U} \phi_i$$

3.5. Since the Eigenvectors are orthogonal:

Note: In what ever direction you are it ill calculate your distance between eyes, width of the nose, Depth of the eye socket, Check bones, Jaw line and Chin.

3.6. Neural Networks and TS-SOM:

Neural Network
Single units to simulate Neurons
Simultaneously Processing
Several inputs and Single output

2) SOM

TS-SOM:- Tree structure self-organizing maps (Figure 5) Each unit of map takes identical inputs Units competes for selection Change of selected node and its neighbors

- a) Training of SOM:
 - (1) Randomly initialized
 - (2) Selection based on few query parameter
 - (3) On selection a node and its neighbors are changed
 - (4) Degree of change reduces with each iteration



Figure 5. Tree Structure Self-Organizing Maps

- b) Algorithm:
 - (1) Calculate weight vector for 1st level.
 - (2) Initialize weight vectors of next levels.

(3) Calculate centroid associated to every node as mean of closest training samples (Figure 6).

(4) Iterate for the next level.



Figure 6. Face Detection in Motion Images.

4. CONCLUSION AND FUTURE WORK

Complete study of the proposed system assuming PCA assumptions not to be true. Investigate whether Eigen faces is a good solution for this problem by comparing with other feature extraction techniques such as DCT. An Eigen faces-based face recognition approach was implemented in MAT LAB. This method represents a face by projecting real images onto a low-dimensional linear subspace-"face space", defined by Eigen faces. A new face is equated to known face classes by computing the distance between their projections onto face space. From clarifications, it has proved that only 15% of Eigen faces with the largest Eigen values are enough for the recognition of a person's face. We can conclude that the test image is absolutely matched with the existing image in the database. Eigen faces for face recognition is best approach for automated attendance system. It is simple, less cost, reliable and reduces man power.

REFERENCES

- [1] Navarrete P; Ruiz-del-Solar J, Interactive Face Retrieval using Self-Organizing Maps, Int. Joint Conf. on Neural Networks–IJCNN, pp.12-17, 2002.
- [2] Lindsay I Smith, A tutorial on Principal Components Analysis.
- [3] Turk M; Pentland A, Eigenfaces for Recognition, Journal of Cognitive Neuroscience, vol.3, no.1, pp.71-86, 1991.
- [4] Ruiz-del-Solar J; Navarrete P, Towards a Generalized Eigenspace-based Face Recognition Framework, 4th Int. Workshop on Statistical Techniques in Pattern Recognition, Windsor, Canada, pp.6-9, 2002.
- [5] James A. Freeman, Simulating Neural Networks.
- [6] Neil J Nielsson; Turk M; Pentland A, Artificial Intelligence.
- [7] Eigenfaces for Recognition. J. Cognitive Neuroscience, vol.3, pp.71-86, 1991.
- [8] M Turk; A Pentland, Eigenfaces for Recognition, Journal of Cognitive Neuroscience, vol.3, no.1, 1991.
- [9] M Turk; A Pentland, Face Recognition Using Eigenfaces, Proc. IEEE Conf. on Computer Vision and Pattern Recognition, pp.586-591, 1991.
- [10] SA Sirohey, Human Face Segmentation and Identification, Technical Report CAR-TR-695, Center for Automation Research, University of Maryland, College Park, MD, 1993

- [11] A Samal; PA Iyengar, Automatic Recognition and Analysis of Human Faces and Facial Expressions: A survey, *Pattern Recognition*, col.25, no.1, pp.65-77, 1992.
- [12] Sirovich L; Kirby M, Low Dimensional Procedure for the Characterization of Human Faces, *Journal of the Optical Society of America A*, vol.4, no.3, pp.519-524, 1987.
- [13] A Pentland; T Choudhury, Face Recognition for Smart Environments, vol.33, no.2, 2000.
- [14] R Chellappa; CL Wilson; S Sirohey, Human and machine recognition of faces: A survey, Proc. of IEEE, vol/83, no.5, pp.705-741, 1995.